

TBIT Ultra Service

Sizing the smallest metal loss defects with our tank bottom inspection service



Highest sensitivity allows for early detection of small features



Competence and reliability in MFL data analysis from our ILI market leadership position



Reduction of hours due to automated feature detection and sizing



Fast inspection turnaround time through on-site reporting



Exceeding inspection compliance requirements

Where corrosion is one of the most common threats to lifetime performance, TBIT Ultra can help ensure tank bottom integrity. Through sensitive detection and diagnosis, the TBIT Ultra service is capable of accurately sizing the smallest metal loss defects and delivers fast results, which inform decisions now and aid with planning for the future.

Detection & Diagnosis

Early detection of the presence or absence of any small defect indications enables operators to obtain more precise corrosion rate determinations, reduces the costs of ownership and extends the inspection interval. The TBIT Ultra Service provides industry leading performance in automated and accurate sizing, including the smallest metal loss defects. The TBIT Ultra Service allows for maximum coverage of the tank floor by using a remote-control tank floor scanner for difficult-to-access areas (e.g. under piping or heating coils). In addition, a dedicated Blind Zone Scanner for areas that otherwise remain uninspected due to the physical limitations of the floor scanner significantly reduces the risk of missing relevant metal loss defects in areas normally not being covered by floor scanners.

Benefits

- Highest sensitivity — 10% metal loss reporting threshold
- Automated defect sizing through signal-based analysis — more reliable and more accurate than manual UT
- Automated internal and external defect discrimination
- High coverage inside the critical zone including annular plates, sketch plates and areas close to the plate and corner welds



- Suitable for use in restricted areas by using remote-control tank floor scanner (e.g. below heating coils and piping)
- Less blind zones: Reduction of uninspected areas through dedicated Blind Zone Scanner
- Fast inspection turnaround time through on-site reporting resulting in less out-of-service time
- Reduction of hours in confined spaces due to automated feature detection and sizing
- Coating removal is not required (for coatings 0.24 inches / 6mm)
- From compliance to performance — exceeding requirements outlined in API653 and EEMUA 159
- Instant access to relevant integrity data and clear recommendations on mitigation and repair
- Data stitching – alignment of data sets from tank floor scanner (TBIT Ultra) and Blind Zone Scanner
- Data integration and visualization in ROSOFT for Tanks data management and planning software

Prescription & Prognosis

“ROSOFT for Tanks” is a versatile data management and planning system that visualizes all inspection findings (from 10% metal loss) and enables quick and easy development of repair scenarios, and corresponding Bills of Material (patch plate sizes, welding lengths,

etc.). Our integrity team provides a short-term prescription and long-term prognosis to help optimize expenditure by providing sound advice on mitigation, repair, and future needs.

Technical Specifications

	TBIT Ultra	Blind Zone Scanner
Detection Threshold Pitting & General Corrosion Pinholes	0.1t Ø2mm [0.08"] and 0.2t	0.2t Ø3mm [0.12"] × 0.2t
Sizing Accuracy Depth	±0.04t	±0.1t
Coating Thickness	Up to 6mm [0.236"] (automatic sizing) 6-10mm [0.236"-0.394"] (detection only)	Up to 2mm [0.08"] (automatic sizing) 2-3mm [0.08"-0.12"] (detection only)
Plate Thickness	4-16mm [0.156"-0.625"]	4-8mm [0.156"-0.315"]
No. of Sensors	1029 (Hall + EC)	270 (Hall + EC)
Internal/External Discrimination	Yes	Yes
Scan Speed	100 m ² /h or 1076 ft ² /h	Less than a minute per blind zone (245mm × 245mm [10" × 10"])

Please note that this specification only applies if certain conditions are in place. For details please refer to the Performance Qualification Reports “ROSEN TBIT Ultra Validation test Version 1.0” and “BZS Validation report”, which are an integral part of this specification. No other party than ROSEN shall be entitled to copy, alter or modify this specification or to use it for own or other purposes or disclose it on to third parties without the prior written consent of ROSEN.

Service Level Specifications

Our TBIT Ultra Service provides different service levels allowing you to choose the solution that meets your needs and budget.

Service Level	Extended	Standard	Essential
Reporting Threshold	10% Ø2mm	20% Ø3mm	40% Ø10mm
ROSOFT for Tanks Reporting including	<ul style="list-style-type: none"> • Floor map • Stripes incl. bitmaps • Floor map of features above 10% • Coordinates • Feature list • Feature statistic • Full data set incl. C-scan • Lift-off and respective coating thickness • Wall thickness 	<ul style="list-style-type: none"> • Floor map • Stripes • Floor map of features above 20% • Coordinates • Feature list • Feature statistic 	<ul style="list-style-type: none"> • Floor map • Stripes • Floor map of features above 40%
Reporting Format	Comprehensive PDF report	Standard PDF report	PDF report (1 page)

ROSEN Swiss AG
Obere Spicherematt 14 · 6370 Stans · Switzerland

Phone: +41-41-618-0300
info@rosen-group.com
www.rosen-group.com

ROSEN-Group_Serviceflyer_TBIT-Ultra_v1-0_2024

© 2024 ROSEN Swiss AG.
All rights reserved.

This document is the property of ROSEN Swiss AG who will safeguard its rights according to the applicable civil and criminal law provisions. No part of this document may be reproduced without the prior written consent of ROSEN Swiss AG.

The information provided in this document is for general informational purposes only and is based on current technical knowledge and experience. It does not constitute any professional advice or any legally binding offer. While every

effort has been made to ensure the accuracy of the information provided, no warranties, guarantees or representations, either expressed or implied, are made as to the completeness, accuracy, reliability, or timeliness of the information.

This document may be updated and amended by ROSEN from time to time due to technical, regulatory and / or legal requirements or changes without prior notice. Only the latest version of this document is applicable; all earlier versions shall cease to be valid.