

# ATEX Compliance

## Certified Instruments for Operation in Explosive Atmospheres



Broad compatibility for pipelines ranging from 6" to 56"



Demonstrate compliance with standards and regulations



Customized tool fleet to meet unique pipe-line requirements

**An explosive atmosphere is a mix of flammable substances in the form of gas, vapor, mist or dust mixed with oxygen under atmospheric conditions; in which, once ignited spreads to the entire unburned mixture.**

In the European Union, ATEX is defined by two main directives: 2014/34/EU, known as ATEX 114, and 1999/92/EC, known as ATEX 137. 2014/34/EU defines requirements and guidelines applicable to equipment intended to be operated in explosion hazard zones. 1999/92/EC is applicable for operators and defines measures and guidelines aimed at ensuring safety and health integrity while operating in areas with potentially explosive atmospheres.

The need to have guidelines to ensure health and safety while working in hazardous environments initiated back in the 1920's driven by mining and the emerging chemical industry. Equipment manufacturers have the obligation to ensure their products are never the source of ignition while operated in hazardous environments. One method to achieving this objective is by avoiding any possible contact between the explosive atmosphere and potential sources of ignition within the equipment. Different guidelines apply to electrical and non-electrical equipment.

ROSEN equipment follows not only guidelines defined by ATEX 114 but also guidelines defined by POF (Pipeline Operators Forum). ROSEN equipment has been certified for working under potentially explosive nonatmospheric conditions.

Operators are also required to apply measures in order to comply with the ATEX directive 1999/92/EC. ATEX zones need to be identified and classified and all personnel must be properly trained and certified. While the operation takes place within the premises marked as ATEX zones, the operator is responsible for its personnel and that of subcontractors. All equipment, materials and accessories have to be ATEX certified to be allowed to operate within the ATEX zone.



Type plate of an ATEX-compliant ROSEN tool



ATEX-compliant 12" Magnetic Flux Leakage Metal Loss ILL tool

ROSEN production quality assurance is certified according to EN ISO/IEC 80079-34:2020, which allows for manufacturing and assembly of equipment with flameproof enclosure (Ex d), pressurized encapsulation bodies (EX p) and intrinsic safety (EX i). ROSEN has a team of qualified experts responsible for handling, documenting and maintaining ATEX relevant equipment and components.

Our commitment to a safe working environment is demonstrated by the extensive fleet of ILI tools matching the above mentioned requirements.

By using a modular approach ROSEN ATEX-compliant ILI tools remain as flexible as the standard tools. We combine state of the art technology already available with ATEX required features, resulting in an ILI tool which is not only as technologically advanced as the standard fleet, but is also fully compliant with ATEX 114 directives. To ensure proper handling, ROSEN also manufactures all required accessories, such as tool status monitoring units, ATEX-compliant cups and discs, launching/receiving units, etc. allowing our personnel and our clients to maintain a safe working environment under full compliance with ATEX directives.

## Benefits

- Operational flexibility despite regulatory requirements/high degree of flexibility for entire tool fleet from 6" to 56"
- Compliant with the requirement of the POF specification 2016 – consideration of atmospheric conditions
- Possible multi- and single-body tool configurations and customization, defined by customer & pipeline requirements

## Technical Specifications

### Standard Operating Specifications

<b>Tool sizes available</b>	6"-56"
<b>Pipeline product</b>	Gas or liquids
<b>Product temperature range</b>	-20 °C to 60 °C (-4 to 140 °F)
<b>Maximum operating pressure</b>	II 2G Ex pxb h IIB T4 Gb
<b>Operating speed range</b>	EPS 09 ATEX 1 184 X
<b>Minimum pipeline bend radius</b>	15 MPa (2176 psi)
<b>Wall thickness range</b>	Up to 3 m/s (8 mph)
<b>Minimum pipeline bend radius</b>	1.5D
<b>Maximum operating time</b>	400 hours
<b>Maximum inspection length</b>	800 km (497 miles)
<b>Available services</b>	<ul style="list-style-type: none"> <li>• Geometry surveys</li> <li>• Dent assessment</li> <li>• XYZ mapping</li> <li>• Metal loss detection</li> <li>• Wall thickness mapping</li> <li>• Crack detection</li> <li>• ... and combinations of the above</li> </ul>

ROSEN Swiss AG  
Obere Spichermatt 14 · 6370 Stans · Switzerland  
Phone: +41-41-618-0300  
info@rosen-group.com  
www.rosen-group.com

ROSEN-Group\_Serviceflyer\_ATEX\_v1-0\_2024

© 2024 ROSEN Swiss AG.  
All rights reserved.

This document is the property of ROSEN Swiss AG who will safeguard its rights according to the applicable civil and criminal law provisions. No part of this document may be reproduced without the prior written consent of ROSEN Swiss AG.

The information provided in this document is for general informational purposes only and is based on current technical knowledge and experience. It does not constitute any professional advice or any legally binding offer. While every

effort has been made to ensure the accuracy of the information provided, no warranties, guarantees or representations, either expressed or implied, are made as to the completeness, accuracy, reliability, or timeliness of the information.

This document may be updated and amended by ROSEN from time to time due to technical, regulatory and / or legal requirements or changes without prior notice. Only the latest version of this document is applicable; all earlier versions shall cease to be valid.