RoCorr MFL-A Ultra Service

In-line Ultra-High-Resolution Metal Loss Detection and Sizing



impact pipeline safety



Reliable assessment of pinholes and complex corrosion



Assess the integrity of your onshore and offshore pipeline assets

Undetected and untreated corrosion within your pipeline assets will lead to performance loss and containment failure. Making in-line inspection (ILI) services a part of your integrated pipeline threat management strategy will help you manage this risk. Our RoCorr Service Suite is designed to detect, evaluate and locate metal loss due to corrosion and associated threats. This allows you to take remedial action before your pipeline integrity suffers.

Drawing on the largest ILI tool fleet in the world, our RoCorr features multiple and flexible options to suit your inspection needs while minimizing impact on pipeline operations. This includes a wide range of sensors that incorporate leading technologies to address your pipeline threats. The data gathering is supported by our unique data analysis and reporting tools, delivered by a dedicated team of experts. RoCorr reduces your corrosion and metal loss threat risk.

Our MFL-A Ultra Service offers an ultra-high resolution approach that overcomes the historically conservative evaluation of metal loss. The MFL-A Ultra Service identifies pinholes down to one millimeter in diameter. It also defines the exact structures of defects, such as complex corrosion. Machine-learning systems and Finite Element Modeling (FEM) bring new standards in data evaluation for ultra-precise results delivery.

- Superior integrity assessment through enhanced accuracy
- Reduction of unnecessary and costly dig-ups
- Ultra-precise evaluation of sizeable data volumes
- Minimizing the impact of inspections on daily operations through:
- Speed control units to maintain full production flow during inspection
- Combined diagnostics solutions to reduce the number of inspection runs required by combining technologies in one ILI tool



Benefits

- Improved sizing accuracies enable most accurate integrity assessments to reduce conservatism and significantly reduce unnecessary digs
- Superior pipeline and defect imaging through enhanced MFL technology with ultra-high definition sensors
- Detailed insights into a breadth of defect morphologies and different corrosion types such as pinhole in pit and pinhole colonies provided by ultra-high resolution sensors
- Enhanced sensor suspension for smoother girth weld passage overcomes long-standing industry limitations
- Well-proven tools deliver consistent data quality with a first run success rate of 95%



Remarks and Features

- Other tool sizes are available on request
- Higher pressure rating available on request
- Tailored solutions with different specifications available
- API 1163 certified services
- CE and ATEX certification available
- Contact ROSEN for more detailed information about the presented service
- Specifications are subject to change, depending on specific requirements or tool configurations

Technical Specifications

Standard Operating Specifications

Tool sizes available	6"-56"
Pipeline product	Liquids
Product temperature range	Up to 65 °C (149 °F)
Maximum operating pressure	15 MPa (2175 psi) 25 MPa (3625 psi) optional
Operating speed range	Up to 2.5 m/s (5.6 mph)
Minimum pipeline bend radius	1.5D
Wall thickness range	5–45 mm (0.19–1.77")

Note: Contact ROSEN for more detailed information.

Performance Specifications

Axial sampling distance		2 mm (0.08")
Circumferential sensor spacing		8 mm (0.31")
Discrimination int./ext.		Yes
Detection of metal loss at POD = 90%	Minimum diameter Minimum depth	10 mm (0.39") 0.8 mm (0.03")
Depth sizing accuracy	At 90% certainty	±0.4 mm (±0.016")
Length sizing accuracy	At 90% certainty	±7 mm (±0.27")
Width sizing accuracy	At 90% certainty	±8 mm (±0.31")
Accuracy of wall thickness measurement	At 90% certainty	±0.2 mm (±0.008")

Note: Contact ROSEN for more detailed information.

Location and Orientation Capabilities

Axial position accuracy from reference marker 1 m on 1000 m (1 ft on 1000 ft) marker distance	1:1000
Axial position from closest weld	±0.1 m (±4")
Circumferential position accuracy	±10°

The axial positioning accuracy specified is based on following criteria: Distance between upstream and downstream marker/reference point < 2000 m (1.2 miles)

Actual above ground distance to both upstream and downstream marker/reference points to be measured and correlated. Negligible difference between pipeline and soil contour

Other Features with POI > 90%

Mid-wall features	Laminations and inclusions minimum diameter	10 mm (0.39")
Deformations	Dents ¹ , wrinkles	Yes
Weld detection	Girth weld, spiral weld, longitudinal weld	Yes
Installations	Minimum diameter	25 mm (1.0")
Bends	Bend radius < 5D/90°	Yes
Repair areas (welded)	Sleeves, patches, attachments	Yes

¹ POI above 90% only reached in combination with geometry inspection, which is usually performed to assure proper tool passage. Without any geometry tool, dents are only identified with a robability between 50% and 90% (maybe).

Note: Specifications are subject to change according to specific requirements. Abbreviations: POD = Probability of Detection; POI = Probability of Identification

ROSEN Swiss AG

Obere Spichermatt 14 · 6370 Stans · Switzerland Phone: +41-41-618-0300 info@rosen-group.com www.rosen-group.com ROSEN-Group_Serviceflyer_RoCorr_MFL-A_Ultra_v1-0_2024 © 2024 ROSEN Swiss AG.

All rights reserved.

This document is the property of ROSEN Swiss AG who will safeguard its rights according to the applicable civil and criminal law provisions. No part of this document may be reproduced without the prior written consent of ROSEN Swiss AG.

The information provided in this document is for general informational purposes only and is based on current technical knowledge and experience. It does not constitute any professional advice or any legally binding offer. While every effort has been made to ensure the accuracy of the information provided, no warranties, guarantees or representations, either expressed or implied, are made as to the completeness, accuracy, reliability, or timeliness of the information.

This document may be updated and amended by ROSEN from time to time due to technical, regulatory and / or legal requirements or changes without prior notice. Only the latest version of this document is applicable; all earlier versions shall cease to be valid.

ROSEN